


- 1: GLAZING MATERIAL**
- | | | |
|-------------------------|--------------------------|--------------------------|
| | INNER | OUTER |
| TEMPERED | <input type="checkbox"/> | <input type="checkbox"/> |
| LAMINATED | <input type="checkbox"/> | <input type="checkbox"/> |
| TEMPERED & LAMINATED | <input type="checkbox"/> | <input type="checkbox"/> |
| OVERALL GLASS THICKNESS | 3/4" | <input type="checkbox"/> |
| | 1" | <input type="checkbox"/> |
| OTHER | _____ | |

- 2: GLAZING COLOR**
- | | | |
|---------|--------------------------|--------------------------|
| CLEAR | <input type="checkbox"/> | <input type="checkbox"/> |
| BRONZE | <input type="checkbox"/> | <input type="checkbox"/> |
| LOW "E" | <input type="checkbox"/> | <input type="checkbox"/> |

- 3: FRAME FINISH**
- | | |
|-----------------|--------------------------|
| MILL | <input type="checkbox"/> |
| BRONZE ANODIZED | <input type="checkbox"/> |
| CLEAR ANODIZED | <input type="checkbox"/> |
| CUSTOM COLOR | _____ |

FOR SELF FLASHING SKYLIGHTS PROVIDE
ROUGH OPENING OR ID OF SKYLIGHT DIMENSION

- | | | |
|------|--------|---|
| QTY: | R.O. = | X |
| QTY: | R.O. = | X |
| QTY: | R.O. = | X |
| QTY: | R.O. = | X |
| QTY: | R.O. = | X |



4" GLASS THERMALLY BROKEN & INSULATED FIXED SELF FLASHING

MINIMUM 3/12 PITCH REQUIRED



AMERICAN SKYLITES
525 113th STREET ARLINGTON, TEXAS 76011
Phone 800.772.7401 Fax 800.445.7282

SPECIFICATIONS		
TEST METHOD	TEST PRESSURE	ALLOWED
AIR INFILTRATION ASTM E283	6.24 PSF (50 MPH)	0.03 CFM/FT
WATER PENETRATION ASTM E547/E331 UNIFORM LOAD ASTM E330	TEST PRESSURE 15.0 PSF POSITIVE 69.0 PSF NEGATIVE 75.0 PSF	NO LEAKAGE 60.0 PSF MIN 40.0 PSF MIN