I: <u>GLAZING MATERIAL</u> INNER OUTER ACRYLIC POLYCARBONATE	OUTER GLAZING INNER GLAZING STRUDED ALUMINUM ALUMINUM ANGLE
2: GLAZING COLOR CLEAR BRONZE WHITE OTHER 3: FRAME FINISH	SEALANT TAPE ROUGH OPENING TO CENTERLINE OF RIDGE BOTH SIDES CONDENSATION GUTTER .060" EXTRUDED ALUMINUM FRAME 3" MOUNTING FLANGE
MILL BRONZE ANODIZED CLEAR ANODIZED CUSTOM COLOR	S. S. FASTENER WITH GROMMET ALUMINUM FRAME
RIDGE MOUNT RO=DIM#1: FROM CURB WALL TO & RIDGE DIM#2: FROM & RIDGE TO CURB WALL DIM#3: OVERALL LENGTH/RUN OF UNIT	SANTOPRENE GASKET 080" EXTRUDED ALUMINUM FRAME 2" X 3" ALUM. TUBE (AS REQUIRED)
RO = X X	ROUGH OPENING (LENGTH)
# BAYS = PITCH = *RIDGE MOUNT MAY REQUIRE PARTIAL FIELD ASSEMBLY. *3.25" SELF FLASHING FRAME	RIDGE MOUNT SELF FLASHING (MODEL RMSF)
*NOTE DIMENSIONS ABOVE AND/OR ON DRAWING. *NOTE # OF BAYS ABOVE. *ROOF PITCH REQUIRED. *ALL SKYLIGHT FASTENERS STAINLESS STEEL. *ALL FRAMING, FLASHING & FASTENERS ARE SUPPLIED BY OTHERS.	AMERICAN SKYLITES Phone: 855.772.7401 Fax: 855.445.7282